Technical data sheet

Corotop Band

Fixing tape for bonding and repairing roof membranes

Single-sided adhesive tape made from highly vapour-permeable polypropylene membrane and acrylic dispersion. Ensures continuity of vapour permeability of the film at the damage location. Resistant to UV light and the weather.

Advantages

- ✓ high adhesive power
- ✓ strong initial grip
- ✓ vapour-permable
- ✓ effectively repairs demages

Application

- ✓ for joining and repairing polypropylene-based roofing membranes
- ✓ gluing on smooth and rough surfaces
- ✓ mainly for outdoors use

Characteristics

Material	polypropylene, acrylic adhesive
Colour	red/white printing
Length	25 m
Width	50 mm

Peel strength of joints	≥ 10 N/25mm
Elongation	40 %
Temperature of application	+5°C to +30°C
Temperature resistance	-30°C to +100°C

Installation

1. Glued surfaces must be dry, free of dust and oil
2. The product should be mounted without tensioning.
3. After laying the tape on the target Surface, press the tape with a spatula or roofing roller.
4. The recommended temperature of application must be observed.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage. Storage at 15-25 °C with rH 40 - 60%.

Packaging

Quantity per box (pcs.):	6
Quantity on a pallet (box/pcs.):	120/720

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.