Technical data sheet

Corotop BigBand

Fixing tape for bonding and repairing roof membranes

Single-sided adhesive tape made of highly vapor-permeable polypropylene membrane and acrylic dispersion. Ensures the continuity of the vapour permeability of the film at the site of damage. Resistant to UV radiation and weather conditions. The BIGBAND version has a split liner, which facilitates the work related to the termination of the roof valey and ridge.

Advantages

- ✓ high adhesive power
- ✓ strong initial grip
- ✓ vapour-permable
- ✓ BIG variant for corners (split liner)

Application

- ✓ for joining and repairing polypropylene-based roofing membranes
- ✓ gluing on smooth and rough surfaces
- ✓ mainly for outdoors use

Characteristics

Material	polypropylene, acrylic adhesive	Peel strength of joints	≥ 10 N/25mm
Colour	red/white printing	Elongation	40 %
Length	25 m	Temperature of application	+5°C to +30°C
Width	240 mm	Temperature resistance	-30°C to +100°C

Installation

1. Glued surfaces must be dry, free of dust and oil
2. The product should be mounted without tensioning.
3. After laying the tape on the target Surface, press the tape with a spatula or roofing roller.
4. The recommended temperature of application must be observed.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage. Storage at 15-25 °C with rH 40 - 60%.

Packaging

Quantity per box (pcs.):	1
Quantity on a pallet (box/pcs.):	120/120

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.