Technical data sheet

Corotop FixPRO

Fixing tape for outdoor applications

Single-sided tape made from polyethylene film and acrylic dispersion adhesive, reinforced with polyester fibre. For bonding and repairing roof membranes and other polypropylene-based construction products. Features increased adhesive strength and higher resistance to harsh conditions. Espetially recommended for bonding in critical areas. Resistant to UV radiation and aging processes.

Advantages

- ✓ reinforced with polyester fibre
- ✓ strong initial grip
- ✓ three months UV resistance
- ✓ high adhesive strength after fixation

Application

- ✓ for joining and repairing roof and facade membranes
- ✓ for polypropylene and polyethylene vapour barriers
- ✓ for bonding films with plastic, concrete and wood elements
- ✓ for indoor and outdoor use

Characteristics

Material	LDPE, włókno poliestrowe, klej akrylowy	Peel strenth of joints	≥ 30 N/25mm
Colour	white/red printing	Elongation	100 %
Length	25 m	Temerature of application	from +5°C to +30°C
Width	60 mm	Temperature resistance	from -30°C to +100°C

Installation

1. Glued surfaces must be dry, free of dust and oil.
2. The product should be mounted without tensioning.
3. After laying the tape on the target Surface, press the tape with a spatula or roofing roller.
4. The recommended temperature of application must be observed.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in coveredmeans of transport, secured against damage. Storage at 15-25 ° C with rH 40 - 60%.

Packaging

Quantity per box (pcs.):	5
Quantity on a pallet (box/pcs.):	175/875

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. Must be observed. This technical data sheet supersedes all previous versions applicable to this product.