Technical data sheet

Corotop PUR

Sealing tape

A self-adhesive sealing tape in the form of cross-linked polyethylene foam with closed cell structure. Designed for sealing the contact points between the roof membrane and counter-battens and roof truss. It eliminates irregularities between the counter-battens, roof membrane and rafters. It is characterised by high thermal insulation.

Advantages

- ✓ good adhesion to smooth and porous surfaces
- ✓ weatherproof
- ✓ prevents water from penetrating the thermal insulation at the membrane penetration points

Application

- ✓ for sealing the contact points between the roof membrane and counter-battens and roof truss

Characteristics

Material	polyethylene
Colour	grey
Length	30m
Width	40/50/60mm
Thickness	3mm

Tensile strength	≥ 740 kPa
Elongation	≥ 9%
Temperature of application	from +5°C to +40°C
Temperature resistance	from -30°C to +100°C

Installation

1. Glued surfaces must be dry, free of dust and oil
2. The product should be mounted without tensioning.
3. Apply the sealing tape to the counter-battens on the side that will stick to the membrane in such a way that the whole surface of the tape covers the counter-battens
4. Nail the counter-battens to the rafters along the fixing points of the rafters, so that each puncture point of the foil is sealed with the tape.
5. The recommended temperature of application must be observed.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage. Storage at 15-25 °C with rH 40 - 60%.

Packaging

Quantity per box-packing (pcs.):	12/18/16
Quantity on a pallet (pcs.):	252/216/192

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.