



Standard Asphalt Flashing

Submittal

Job Reference

Job Name

Job Location

Submitted By

Submitted By

Date

Phone

Date

Phone

Introduction

Kingspan GreenGuard® Standard Asphalt Flashing is an economical, self-adhering flashing membrane comprising a polyolefin film with a rubber-modified asphalt adhesive. It is designed to seal the interface around wall penetrations such as windows, doors, pipe penetrations and other areas that may require a weatherproof seal.

- Blocks water infiltration around windows and doors
- Rubber-modified asphalt adhesive
- Economical self-adhering membrane

Compliance

AAMA 711.

GreenGuard®

Standard Asphalt Flashing

Handling & Storage

Store boxes containing Kingspan GreenGuard® Standard Asphalt Flashing in a clean, dry area without prolonged, direct exposure to sunlight or heat. Kingspan GreenGuard® Standard Asphalt Flashing has a shelf life of approximately 18 months.

WARNING: This product is combustible. A protective barrier or thermal barrier is required as specified in the appropriate building code. Protect it from exposure to open flame or other ignition sources during shipping, storage and installation.

WARNING: The release paper of Kingspan GreenGuard® Standard Asphalt Flashing is slippery and should not be walked on at any time. Discard release paper in a designated container.

Installation

To obtain the best adhesion, Kingspan GreenGuard® Standard Asphalt Flashing should be installed over surfaces that are free of dirt and moisture. Placement by hand, then it is necessary to apply strong pressure with a j-roller to ensure adhesion.

Product Data		
Property	Test Method	Value
General		
Nominal Thickness	(in)	0.020
	(mils)	20
Nominal Length (ft)		75
Nominal Width (in)		6
Backing Material		Polyolefin
Adhesive		Rubber Modified Asphalt
Release Liner		Yes
Application Temp., Min. (°F)		40
Recommended Service Temp., Min. (°F)		160
UV Exposure (days)		90
Shelf Life		18 Months

For more information on specific building product recommendations and installation guidelines, contact your Kingspan Insulation LLC representative.

Kingspan Insulation LLC believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Kingspan Insulation LLC does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. No warranty, express or implied, is given as to the merchantability, fitness for particular purpose, or otherwise with respect to the products referred to.



Please scan the QR code for the most recent product information.

Kingspan Insulation LLC

6120 Powers Ferry Road NW | Suite 350
Atlanta | Georgia 30339

T: +1 (800) 241 4402

E: info@kingspaninsulation.us

www.kingspaninsulation.us

www.kingspaninsulation.ca

© Kingspan, the G Device and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved.

© GreenGuard is a Registered Trademark of the Kingspan Group plc in the US. All rights reserved.
[kingspan-green-guard-standard-asphalt-flashing-submittal-en-us-ca-v1](#)

Version 1 - 11/2025

