



Product Safety Information

Although the REACH Regulation does not require a Safety Data Sheet to be provided for Therma™ products, as they are considered articles under the Regulation, this Product Safety Information Sheet has been prepared to reflect the primary SDS requirements as set out in Annex II to Regulation (EC) No 1907/2006 (REACH), as amended at the date of the publication, as they might reasonably apply to articles.

1 Identification of the product and of the company / undertaking

1.1 Product Identifier

Kingspan Thermapitch® TP10;
 Kingspan Thermawall® TW50;
 Kingspan Thermawall® TW52;
 Kingspan Thermawall® TW55;
 Kingspan Thermawall® TW56;
 Kingspan Thermafloor® TF70;
 Kingspan Therमारoo® TR24;
 Kingspan Therमारoo® TR26;
 Kingspan Therमारoo® TR27;
 Kingspan Thermataper® TT46;
 Kingspan Thermataper® TT47.

1.2 Relevant identified uses of the product

Fibre-free cored rigid thermoset polyurethane or polyisocyanurate insulation for building fabric and building services applications. No uses advised against on physical, health or environmental grounds based on the provisions of the REACH Regulation.

1.3 Details of the supplier of the Product Safety Information Sheet

Company Name: Kingspan Insulation Limited
 Company Address: Castleblayney, County Monaghan.
 Tel: +353 (0) 42 979 5000
 Email: info@kingspaninsulation.ie
 Website: www.kingspaninsulation.ie

1.4 Technical Support contact details

Tel: +353 (0) 42 975 4297
 Email: technical@kingspaninsulation.ie

2 Hazards Identification

2.1 Classification

The product article is not classified as hazardous.

2.2 Label elements

In line with the lack of classification, there are no specific labelling requirements.

2.3 Other hazards

Not applicable.

3 Composition information

Core:	Rigid thermoset urethane (PUR or PIR as defined by EN 13165) insulation.
Alternative facings:	Composite foil (TP10, TR26, TT46, TW50, TW55, TW56, TF70). Bitumen coated glass tissue (TR24). Coated glass tissue (TR27, TT47). Plasterboard (TW52, TW56).

Further information on facings available upon request.



4 First aid measures

4.1 Description of first aid measures

Inhalation:	Remove the person to fresh air.
Skin:	Wash carefully using soap and water or a proprietary cleanser to remove.
Eyes:	Dust particles should be removed by flushing with clean water.
Ingestion:	Drink plenty of water if dust particles are accidentally ingested.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation:	Possible irritation or soreness in throat and nose.
Skin:	Temporary irritation or rash. Non-sensitising. When facings containing glass fibres are handled, skin irritation may occur.
Eyes:	Temporary irritation or inflammation.
Ingestion:	No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if needed. Treat symptomatically.

5 Firefighting measures

5.1 Extinguishing media

Suitable media:	Water spray (fog), foam, CO ₂ or dry chemical.
Unsuitable media:	Not applicable.

5.2 Special hazards arising from the product

It is prudent to take precautions against ignition, fire spread and combustion products. As with all organic products, PIR will combust under severe fire conditions, where various oxides of carbon may form. Do not incinerate waste foam in an open environment. Do not inhale fumes; Fire fighters should attack the fire according to the combustible materials present and use breathing apparatus. Cardboard and plastic packaging materials are combustible. Store away from all possible sources of ignition.

5.3 Advice for firefighters

Firefighters should use self-contained breathing apparatus and saturate burning foam with water from a spray nozzle. Dust is classified as weakly explosive (St. Class 1).

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid the creation of airborne dust. If dust is generated, use approved respiratory protective equipment. Do not breathe dust (see Section 8).

6.2 Environmental precautions

Do not release collected dust to drains or waterways (see Section 13 for Disposal considerations).

6.3 Methods and material for containment and cleaning up

Prevent dust generation and use dust sheets before cutting to capture any dust generated. If dust does accumulate use vacuum cleaner (HEPA-filtered) or dampen with water spray.

6.4 Reference to other sections

See Section 8 for PPE.
See Section 13 for Disposal considerations.

7 Handling and storage

7.1 Precautions for safe handling

During cutting procedures, wear appropriate PPE. Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used. If dust generation persists over a sustained period in an enclosed space, the level of dust should be monitored in line with local regulations.

7.2 Conditions for safe storage, including any incompatibilities

Store in original packing in a location free from any ignition hazard such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat. Traces of ethanol may be released from material that is freshly produced.

Keep product protected from the elements. Ensure stability of stack and provide adequate aisle space for access between stacks.

8 Exposure controls / personal protection

8.1 Control parameters

There are no specific occupational exposure limits (OELs) for PUR or PIR dust itself, but best practice is not to exceed 3 mg/m³ based on an 8-hour time-weighted average (TWA).

8.2 Exposure controls

Inhalation: During cutting procedures, wear adequate and suitable recommended respiratory protective equipment (RPE), such as particulate respirator with dust filter.

Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used.

Hands: It is recommended that gloves be worn when handling the products.

Eyes: Eye protection recommended during mechanical cutting. When installing a product with reflective foil facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.

Skin: Non-sensitising. It is recommended to wear gloves when handling the products. When installing a product with reflective facings in bright sunlight, it is advisable to consider skin protection from UV.

Other: The products are non-load bearing. Access and work should not be carried out on unsupported boards.

The smooth facing used on some Therma™ products can be slippery underfoot when wet.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Yellow foam with composite foil, glass reinforced perforated cellulose, glass tissue, bitumen coated glass tissue or coated glass tissue facings.

Odour: Negligible.

pH: Neutral under normal conditions.

Melting point: Not applicable.

Flash point: Not applicable.

Insulation density: Typically 25-60 kg/m³.

Solubility in water: Insoluble.

Solubility in organics: Some liquids may cause swelling.

Other data: None.

9.2 Other information

No additional chemical or physical properties to report.

10 Stability and reactivity

10.1 Reactivity

Unreactive during normal use (see Section 7).

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Not reactive.

10.4 Conditions to avoid

None specified.

10.5 Incompatible materials

None specified.

10.6 Hazardous decomposition products

Not applicable.

11 Toxicological Information

11.1 Information on toxicological effects

There are no known adverse health effects arising from handling or using Kingspan Therma™ insulation as supplied.

11.2 Information on other hazards

No additional information available.

12 Ecological information

12.1 Toxicity

The products are chemically stable in water and soil.

12.2 Persistence and degradability

PUR is not biodegradable and in common with most polymer materials will be persistent in the environment because of its durability.

12.3 Bio-accumulative potential

None anticipated since the product is a chemically inert polymeric matrix.

12.4 Mobility in soil

No anticipated mobility.

12.5 Results of PBT and vPvB assessment

Testing inappropriate for articles.

12.6 Endocrine disrupting properties

No data available.

12.7 Other Adverse Effects

Blowing agents used in the Kingspan Therma™ range of products have negligible ozone depletion potential (ODP) and low (below 5) global warming potential (GWP).

13 Disposal considerations

13.1 Waste treatment methods

Product dust created in the installation process should be avoided or otherwise minimised to extent possible. Dispose of dust responsibly in line with the precautions set out in Sections 7 and 8.

Waste, including packaging, should be disposed of in accordance with the Waste Hierarchy – Reduce, Re-Use, Recycle. Refer to local waste handling legislation and carry out any required waste classification assessment required under local legislation and regulations.

With respect to disposal, observe usual safety precautions with polythene bags, wrapping and packaging.

14 Transport information

Read this section in conjunction with Section 7.

Ensure security of load and where necessary sheeting / roping should be used.

It is recommended that mechanical lifting equipment is used when moving bulk quantities.

15 Regulatory information

15.1 Safety, health and environmental regulations / legislation specific for the product

The product itself is not covered by the Classification Labelling and Packaging Regulation (CLP).

15.2 Chemical safety assessment

No assessment required.

16 Other information

The information contained here is offered in good faith and is based on our current knowledge.

We thereby maintain the right to update and amend this document as necessary.

The information should not be taken as a guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.

The wearing of appropriate safety equipment is strongly recommended as a precaution and the product should only be used in its design application. Please refer to Sections 7 and 8 for safe handling and appropriate safety measures.

Users should visit the Kingspan Insulation website or contact the Kingspan Insulation Technical Service Department to ensure information is current.

This data sheet does not constitute a workplace assessment. The information provided represents the state of our knowledge regarding this material at the date of its publication. The information provided does not constitute a product specification and no warranty expressed or implied is hereby made.

The information relates only to the specific material designated when used in applications it has been designed for. This information may not be valid for such material used in combination with any other materials or in any other processes, unless specified in the text.

Contact details

Kingspan Insulation Ltd

Castleblayney | County Monaghan

T: +353 (0) 42 979 5000

E: info@kingspaninsulation.ie

www.kingspaninsulation.ie

For individual department contact details please visit

www.kingspaninsulation.ie/contact



For the most up-to-date version of this brochure, please scan or click [here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.ie.

The information contained in this brochure is believed to be correct at the date of publication. Kingspan Insulation Limited ("Kingspan Insulation") reserves the right to alter or amend the product specifications without notice due to continuous improvement commitments. There may also be relevant changes between publications with regard to legislation, or other developments affecting the accuracy of the information contained in this brochure. Product thicknesses shown in this document should not be taken as being available ex-stock and reference should be made to the current Kingspan Insulation price-list or advice sought from Kingspan Insulation's Customer Service Department. The information, technical details and fixing instructions etc. included in this literature are given in good faith and apply to uses described. Kingspan Insulation does not accept responsibility for issues arising from using products in applications different from those described within this brochure or failure to correctly follow the information or instructions as described within this brochure. Recommendations for use should be verified with a suitable expert or professional for suitability and compliance with actual requirements, specifications and any applicable laws and regulations. For other applications or conditions of use, Kingspan Insulation offers a technical advisory service (see above for contact details), the advice of which should be sought for uses of Kingspan Insulation products that are not specifically described herein. Please check that your copy of this literature is current by contacting the Kingspan Insulation Marketing Department.

© Kingspan, Thermapitch, Therमारoof, Thermataper, ThermaWall, Thermafloor and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries. All rights reserved.

™ Therma is a Trademark of the Kingspan Group plc.

Registered in Ireland, No. 54621. Registered Office: Bree Industrial Estate, Castleblayney, Co. Monaghan, Ireland. VAT IE4575069I.

