

Therma™ TR27

Insulation for Flat Roofs Waterproofed with Fully Adhered Single-Ply and Cold Liquid Applied Waterproofing



- Rigid thermoset insulation
- Fully compatible with most fully adhered single-ply waterproofing systems
- Ideal with most green roof systems
- Easy to handle and install
- Ideal for new build and refurbishment
- Manufactured with a blowing agent that has zero ODP (contains no CFC and HCFC) and GWP ≤5

Product information

Product description

Kingspan Therma™ TR27 comprises of fibre-free rigid thermoset polyisocyanurate (PIR) insulation core, faced on both sides with a coated glass tissue based facing, autohesively bonded to the insulation core during manufacture.

Technical Specifications

Property	Result
	General
Product Thickness*	Refer to Kingspan Insulation for current stock and non-stock sizes
Board Length (mm)*	2400
Board Width (mm)*	1200
Compressive Stress (BS EN 826: 2013)	Exceeds 100 kPa for thickness <120mm and exceeds 90kPa for thickness 120-170mm @ 10% compression
Apparent Density (BS EN 1602: 2013)	32 Kg/m ³
	Thermal
Thermal Conductivity (ASTM C518-21)	0.022 W/m.K at 23°C mean temperature

* Standard manufacturing tolerance may apply, for more information contact Kingspan Insulation.

FM Approval

Kingspan Therma™ TR27 is certified to Examination Standard FM 4470 for flat roof solutions. Please contact the Kingspan Insulation for further confirmation. Not all thicknesses and sizes are covered by the FM Approval.



General

Daily Working Practice

- At the completion of each day's work, or whenever work is interrupted for extended periods of time, a night joint must be made in order to prevent water penetration into the roof construction.

Cutting

- Cutting should be carried out either by using a fine-toothed saw or by scoring with a sharp knife, snapping the board over a straight edge and then cutting the facing on the other side.
- Ensure accurate trimming to achieve close-butting joints and continuity of insulation.

Availability

- Please contact Kingspan Insulation to enquire about the availability of Kingspan Therma™ TR27.

Packaging and Storage

- The polyethylene packaging of Kingspan Insulation products, which is recyclable, should not be considered adequate for outdoor protection.
- Ideally, boards should be stored inside a building. If, however, outside storage cannot be avoided, then the boards should be stacked clear of the ground and covered with an opaque polythene sheet or weatherproof tarpaulin. Boards that have been allowed to get wet should not be used.

Health and Safety

- Please refer MSDS, For more information contact Kingspan Insulation.

Warning – do not stand on or otherwise support your weight on this board unless it is fully supported by a load-bearing surface.

Kingspan Company for Manufacturing

Building No- 8529 | 3rd Industrial City |
Postal Code 34857 | Saudi Arabia | Dammam
T: +966 9200 15349
E: info.ksa@kingspaninsulation.com

www.kingspan.com/sa/en

To ensure you are viewing the most recent and accurate product information, please visit this link <https://www.kingspan.com/sa/en/products/insulation-boards/roof-insulation-board/tr27/?s=d>

© Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc. All rights reserved.

TM Therma is a Trademark of the Kingspan Group plc.

No rights can be derived from this document. Changes, typesetting and printing errors reserved. This version replaces all previous versions.

