



# Declaration of Performance

Kingspan Thermarroof® TR24

1002.CPR.2013.TR24.011

Unique identification code of the product-type:

**Kingspan Thermarroof® TR24**

Intended use/es:

**Thermal insulation for buildings**

Manufacturer:

**Kingspan Insulation Ltd, Bree Industrial Estate, Castleblayney, Co Monaghan, A75 X966**

System/s of AVCP:

**System 4 for Reaction to Fire, System 3 for all other properties**

Designated technical specification:

**EN 13165:2012+A2:2016**

Notified body/ies:

**FIW Munchen (0751)**

Essential characteristics		Performance
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	$d_N$ 35mm 1.25
		$d_N$ 40mm 1.45
		$d_N$ 50mm 1.85
$d_N$ 60mm 2.20		
$d_N$ 70mm 2.55		
$d_N$ 80mm 3.20		
$d_N$ 90mm 3.60		
$d_N$ 100mm 4.00		
$d_N$ 110mm 4.40		
$d_N$ 120mm 5.00		
$d_N$ 130mm 5.40		
$d_N$ 140mm 5.80		
$d_N$ 145mm 6.00		
$d_N$ 150mm 6.25		
Thermal resistance	Thermal conductivity $\lambda_D$ (W/(m.K))	$d_N < 80$ mm 0.027
		$d_N \geq 120$ mm 0.024
Thermal resistance	Thickness tolerance	T2
Reaction to fire	Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	Thermal resistance as table above
	Thermal conductivity $\lambda_D$ (W/(m.K))	$d_N < 80$ mm 0.027 $d_N 80-119$ mm 0.025 $d_N \geq 120$ mm 0.024
	Durability characteristics	NPD
	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1



# Declaration of Performance

	Deformation under specified compressive load and temperature conditions	NPD
	Determination of the aged values of thermal resistance and thermal conductivity	$\lambda_D$ 0,024, 0.025, 0,027 W/m-K
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR80
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing combustion	Glowing combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....  
Siobhan O'Dwyer  
Managing Director, Ireland  
Date signed: 28<sup>th</sup> May 2025  
Issue Number: 011



## Declaration of Performance



For the most up-to-date version of the Declaration of Performance please scan or [click here](#)

To access pre-existing product information or information relating to previously sold/discontinued products please email [info@kingspaninsulation.ie](mailto:info@kingspaninsulation.ie)