

## UK Declaration of Performance

Kingspan K-Stop® Putty Pad

1001.CPR.KStopPuttyPad\_UK.001

Unique identification code of the product-type:  
Intended use/es:

Kingspan K-Stop® Putty Pad  
A fire rated sealant supplied as a non-setting putty in the shape of an intumescent sheet. It can be hand worked into electrical socket boxes.

Manufacturer:

Kingspan Technical Insulation Limited,  
Harvey Rd,  
Basildon,  
SS13 1QJ  
System 1

System/s of AVCP:

EAD 350454-00-1104

Harmonised technical specification:

0843-UKTA-23/0018

UKTA number:

UL International (UK) Ltd

Technical Assessment Body:

UL International (UK) Ltd 0843

Notified body:

| Product type: Intumescent sheet  |   | Intended use: Penetration seal                      |  |
|--|---|---|--|
| Assessment Method  | Essential Characteristics                                   | Product Performance                                 |  |
| <b>BWR 2 Safety in case of fire</b>  |   |   |  |
| EN 13501-1   | Reaction to fire  | NPD   |  |
| EN 13501-2   | Resistance to fire  | 0843-UKTA-23/0018<br>Annex A                        |  |
| <b>BWR 3 Hygiene, health and environment</b>   |   |   |  |
| EN 1026  | Air permeability  | 0843-UKTA-23/0018<br>Annex B                        |  |
| EAD 230454-00-1104,<br>Annex C   | Water permeability  | NPD   |  |
| Declaration of manufacturer<br>& EN 16516  | Content, emission and/or release of<br>dangerous substances | Use categories: IA1<br>Declaration of manufacturer  |  |
| <b>BWR 4 Safety in use</b>   |   |   |  |
| EOTA TR 001:2003   | Mechanical resistance and stability                         | NPD   |  |
| EOTA TR 001:2003   | Resistance to impact/movement                               |   |  |
| EOTA TR 001:2003   | Adhesion  |   |  |
| EAD 350454-00-1104,<br>Clause 2.2.9  | Durability  | Z <sub>2</sub>                                      |  |
| <b>BWR 5 Protection against noise</b>  |   |   |  |
| EN 10140-1,2,4,5 /<br>EN ISO 717-1   | Airborne sound insulation                                   | R <sub>w</sub> (C;C <sub>tr</sub> )= 67 (-2;-7) dB* |  |
| <b>BWR 6 Energy economy and heat retention</b>   |   |   |  |
| EN 12664, EN 12667, EN<br>12939, EN ISO 8990, EN<br>ISO 6946, EN ISO 14683,<br>EN ISO 10211, EN ISO<br>10456 | Thermal properties  | NPD   |  |
| EN ISO 12572, EN 12086,<br>EN ISO 10456  | Water vapour permeability                                   | NPD   |  |

\*Applicable only for K-Stop Putty Pads in socket boxes  
NPD = No performance determined



# UK Declaration of Performance

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Note: Conformity assessment activities undertaken by EU-recognised Conformity Assessment Bodies before 31 December 2022 are allowed to declare existing product types as compliant with UKCA requirements.

This declaration of performance is issued, in accordance with EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020).

Signed for and on behalf of the manufacturer by:

.....  
Andrew Bacon  
Managing Director  
Basildon, England, UK  
Date signed: 14/08/2025  
Issue Number 001

To check that you have the latest version of this DoP please visit [www.kingspanpassivefireprotection.co.uk](http://www.kingspanpassivefireprotection.co.uk)

To access pre-existing product information or information relating to previously sold/ discontinued products please email [literature@kingspaninsulation.co.uk](mailto:literature@kingspaninsulation.co.uk).